

## NX3225GA

For OA / AV

### ■ Features

A small surface-mount type crystal unit, especially suited for small-sizing requirements.

- Compact and thin. (3.2 x 2.5 x 0.75 mm typ.)
- Excellent environmental characteristics, including heat and shock resistance.
- Excellent electrical performance for OA (office automation) and AV (audiovisual) applications.
- Meets the requirements for re-flow profiling using lead-free solder.



**RoHS Compliant**  
Directive 2011/65/EU

### ■ Specifications

Item	Model	NX3225GA
Nominal Frequency		9.840 to 50 MHz
Overtone Order		Fundamental
Frequency Tolerance (25 ±3 °C)		±20 × 10 <sup>-6</sup>
Frequency versus Temperature Characteristics (with reference to +25 °C)		±30 × 10 <sup>-6</sup>
Operating Temperature Range		-40 to +85 °C
Storage Temperature Range		-40 to +85 °C
Equivalent Series Resistance		Refer to *1
Level of Drive		10 μW (Max. 200 μW)
Load Capacitance		8pF

The above specifications are standard for this NDK product.


### ■ How to Specify an Order

When ordering our products, specify them with an "Ordering Code" that consists of the following :

[Model name] - [Frequency (Max : 9 digits)] M - [Number for specifying an order]      Example NX3225GA-27.000M-STD-CRG-2

If you have any queries concerning our standard frequencies and numbers for specifying orders, please contact our sales representatives or visit our homepage (<http://www.ndk.com/>).

### ■ Dimensions



#### \*1 Equivalent Series Resistance

Nominal frequency (MHz)	Equivalent Series Resistance max. [Ω]
9.840 to 12	200
12 to 13	100
13 to 20	80
20 to 50	50